

Water-based Flexo

Water-based Flexo ink range suitable for general label

printing. **Characteristics**

- Excellent adhesion properties
- Fast drying
- Excellent printability
- Water-reducible
- High colour strength
- Excellent rub/scratch resistance

Substrates

Suitable for a wide range of substrates including:

- Coated PE and PP
- Coated papers and board
- Plastic Substrates
- Thermal Substrates

Process Flexo Plus Low-M

	Article code	Light
Transparent White	...	-
Opaque White	...	8
Yellow*	...	4-5
Orange	...	5
Bright Red	...	5
Rubine Red*	...	5
Rhodamine	...	3
Violet	...	3
Process Blue*	...	8
Green	...	8
Black*	...	8

*Can be used as a Process Set

Application

The Mix well before use.

Anilox Selection:

80-160 l/cm (200-400 lpi) volume 6-10 cm³/m²

Minimum dryer temperature – 50°C

Clean equipment immediately after use.

Storage

Containers should be tightly closed immediately after use. All products, including uncontaminated press returns and unopened containers, should be stored at temperatures between 5°C and 25°C.

Health & Safety

Please refer to relevant SDS for information on labelling classifications, waste product and container disposal, and personal protection measures.

This technical instruction sheet is designed for your information and reference. It is based on and conforms to our current knowledge. However as actual application is affected by many factors over which we have no control, we are not liable for printing failures.