

Replenisher for Thermal Positive CTP Plates

Ready to use replenisher. Formulated, developed and specially recommended for Nova Offsetplates **Triton Pro-EU** (and other Thermal Nova Offsetplates) in combination with our Nova Verde Developer. The simultaneous use of the Nova Verde Developer and Replenisher, which is a **"Low Chem System"**, provides a significant advantage in reducing the volume of chemical used and chemicals that has to be recycled.

Product Usage

Replenisher for Thermal Positive CTP Plates
- ready to use.

Directions

Replenishing rate: 50 - 70 ml/m²,

Antioxidant Stand-by ON: 40 - 60 ml/h.
Antioxidant Stand-by OFF: 40 - 60 ml/h.

Features

High productivity in square meters developed -
cost efficient;

Universal in use - for all popular positive
Thermal CTP Plates (non-closed systems);

No or very low residues in the processor tank

Technical Specifications

Form:	liquid
Density:	1.086 g/cm ³
Colour:	transparent
Odour:	neutral
Water miscible:	yes
pH-value:	> 13
Labelling:	H315

Packaging

20 litre can, 200 litre drum
Other packaging on request

Storage and Shelf Life

Storage: not under 6°C, not above 40°C
Shelf life: 12 months
Keep container tightly closed
Keep away from direct sun light

